

# UniGray™ CNL & HCNL

Integral pressure-compensated, continuously self-flushing, anti-siphon and anti-drain mechanism dripper, ideal for greenhouses, and permanent applications that require intensive irrigation scheduling. Dripline colored light gray for minimal solar radiation absorption.

→ 16010 - 16012 - 20010 - 20012



Pressure-compensated



Anti-drain mechanism



Self-flushing mechanism

## / Benefits & Features

- **Pressure-compensated** Precise and equal amounts of water delivered over a broad pressure range, ensuring 100% uniformity of water and nutrient distribution along the laterals.
- **Anti-siphon mechanism** Prevents contaminants from being drawn into the dripper, making it ideal for sub surface applications.
- **Anti-drain mechanism (CNL & HCNL)** Eliminates drainage and refill effect, and improves efficiency in pulse irrigation even in steep topography .
- **Continuously self-flushing** Flushes debris throughout operation, while ensuring constant dripper operation even in challenging water quality.
- **Physical root barrier** Better protection against root intrusion, utilizing unique dripper design that creates physical barriers protecting the dripper from root growth into its labyrinth.
- **Wide filtration area** Ensures optimal performance even under harsh water conditions, preventing the entrance of sediment into the labyrinths.
- **Wide water passages** TurboNet™ labyrinth ensures wide water passages, large deep and wide cross-section that improves clogging resistance. The water is drawn into the dripper from the stream center, preventing the entrance of sediments into the drippers.
- **Light gray color coded** The light gray on the outer surface makes it absorb less energy and takes advantage of the radiation inside the greenhouse.

# / Specifications

- Pressure-compensated range according to tables below.
- Largest filter in the industry. Recommended filtration: 130 micron / 120 mesh. Filtration method selected based on the kind and concentration of dirt particles contained in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclone should be installed before the main filter. Where sand/silt/clay solids exceed 100 ppm, pre treatment it should be applied following Netafim™ expert instructions.
- Double TurboNet™ labyrinth with large water passage.
- Weldable into thick wall driplines (1.00, 1.20 mm).
- Injected dripper, very low CV with injected silicon diaphragm.
- High UV resistant. Resistant to standard nutrients used in agriculture.
- Compliance ISO 9261 international standards.

## → Drippers technical data - CNL Model

Flow rate* (l/h)	Working pressure range (bar)	Water passages dimensions width-depth-length (mm)	Filtration area (mm <sup>2</sup> )	Constant K	Exponent* X	Recommended filtration (micron)/(mesh)	Shut off pressure (bar)
0.70	1.0 - 4.0	0.70 x 0.65 x 40	110	0.70	0	130/120	0.14
1.00		0.83 x 0.74 x 40	130	1.00	0	130/120	0.14
1.60		1.09 X 0.76 x 40	130	1.60	0	130/120	0.14
2.30		1.26 x 0.93 x 40	130	2.30	0	130/120	0.14
3.50		1.59 x 1.07 x 40	150	3.50	0	130/120	0.14

\* Within working pressure range

## → Driplines technical data - CNL Model

Model	Inside diameter (mm)	Wall thickness (mm)	Outside diameter (mm)	Max. working pressure (bar)	Max. flushing pressure (bar)	KD
16010	14.20	1.00	16.20	3.5	4.6	1.30
16012	14.20	1.20	16.60	4.0	5.2	1.30
20010	17.50	1.00	19.50	3.5	4.6	0.40
20012	17.50	1.20	19.90	4.0	5.2	0.40

## → Driplines package data (on bundled coil) - CNL Model

Model	Wall thickness (mm)	Distance between drippers (m)	Coil length (m)	Average* coil weight (kg)	Coils in a 40 feet container (units)	Total in a 40 feet container (m)
16010	1.00	0.15 to 1.00	500	22.2	330	165000
16012	1.20	0.15 to 1.00	400	21.2	352	140800
20010	1.00	0.15 to 1.00	300	17.4	330	99000
20012	1.20	0.15 to 1.00	300	20.2	330	99000

\* Calculated weight average. For further details see "Average Coil Weight Disclaimer"

→ Drippers technical data - HCNL model

Flow rate* (l/h)	Working pressure range (bar)	Water passages dimensions width-depth-length (mm)	Filtration area (mm <sup>2</sup> )	Constant K	Exponent* X	Recommended filtration (micron)/(mesh)	Shut off pressure (bar)
0.85	1.5 - 4.0	0.70 x 0.65 x 40	110	0.85	0	130/120	0.25
1.25		0.83 x 0.74 x 40	130	1.25	0	130/120	0.25
2.00		1.09 X 0.76 x 40	130	2.00	0	130/120	0.25
2.90		1.26 x 0.93 x 40	130	2.90	0	130/120	0.25
4.40		1.59 x 1.07 x 40	150	4.40	0	130/120	0.25

\* Within working pressure range

→ Driplines technical data - HCNL model

Model	Inside diameter (mm)	Wall thickness (mm)	Outside diameter (mm)	Max. working pressure (bar)	Max. flushing pressure (bar)	KD
16010	14.20	1.00	16.20	3.5	4.6	1.30
16012	14.20	1.20	16.60	4.0	5.2	1.30
20010	17.50	1.00	19.50	3.5	4.6	0.40
20012	17.50	1.20	19.50	4.0	5.2	0.40

→ Driplines package data (on bundled coil) - HCNL model

Model	Wall thickness (mm)	Distance between drippers (m)	Coil length (m)	Average* coil weight (kg)	Coils in a 40 feet container (units)	Total in a 40 feet container (m)
16010	1.00	0.15 to 1.00	500	22.2	330	165000
16012	1.20	0.15 to 1.00	400	21.2	352	140800
20010	1.00	0.15 to 1.00	300	17.4	330	99000
20012	1.20	0.15 to 1.00	300	20.2	330	99000

\* Calculated weight average. For further details see "Average Coil Weight Disclaimer"

## / Drippers flow rate vs working pressure

In order to calculate the right flow rate of each dripper, under different working pressures, we use the following formula:

$$Q = K * P^X$$

Where:

Q = Dripper flow rate (liters/hour)

K = Constant (each dripper has his singular constant and must be defined by the dripper producer)

P = Real working pressure (meter)

X = Exponent (each dripper has its singular exponent and must be declared and defined by the dripper producer)

\*ISO 9261 require from the manufacturer to declare the constant K and dripper exponent

In all Netafim™ pressure-compensated drippers - including UniRam™ (shown in this document) – the dripper exponent X is equal to 0 [zero] (within the pressure range defined for each of the drippers), so the right flow rate of the dripper will be always equal (+/- 7% as defined by the international standard: ISO 9261).

Each dripper has a compensation range which includes minimum and maximum pressure; under the minimum pressure defined, the dripper will perform as non-pressure-compensated dripper and provide flow that increases with the pressure increase until reaching the minimum defined limit working pressure.

If the Netafim™ pressure-compensated drippers are exposed to a higher pressure than the defined maximum pressure, the drippers will continue to regulate the flow rate, but become more sensitive to clogging, usually the maximum working pressure of the drippers are determined by the driplines limitations (diameter and wall thickness) and most importantly the pipe and its associated connections.

## / Max. lateral length

Flow Variation (FV) expresses the flow variation between the dripper “sensing” the highest pressure and the one “sensing” the lowest pressure in an irrigation block (zone).

These drippers will not always be the first and last drippers on the dripline.

$$FV \% = (Q_{max} - Q_{min}) / Q_{max} * 100$$

\*International standards define 10% flow variation to be considered as uniform irrigation.

In order to calculate the maximum run lengths that can be planned for specific dripline (considering all the hydraulic factors influencing the flow within the same dripline), we use a calculation software that was developed by Netafim™ based on Darcy-Waisbach formulas + years of design experience and cooperation with academic institutes.

All the tables presented in this document are for initial reference only; the exact run length of the driplines is obtained from design software that considers various hydraulic factors in the entire system.

There might be small variance between the different software's in the market due to the calculation method and assumptions each software is using. For an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

As we have already seen, pressure-compensated drippers of Netafim™ will provide equal flow irrespective of the working pressure, therefore, the factors that are affecting the dripline run lengths will be: the dripline inlet pressure, the minimum working pressure set for the dripper and the slope.

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 0.70 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	83	112	135	153	168	180	190	197	204
	2.0	111	154	190	221	248	271	291	310	326
	2.5	130	182	227	267	302	334	362	388	411
	3.0	145	204	256	303	345	383	418	449	478
	3.5	158	223	281	333	380	424	463	500	534
	4.0	169	239	302	359	412	459	503	545	583

Flat terrain	1.5	96	137	176	213	247	279	310	340	369
	2.0	121	174	224	270	314	356	395	434	471
	2.5	139	200	257	311	361	410	456	500	543
	3.0	153	221	284	343	400	453	504	554	600
	3.5	165	239	306	371	431	489	545	598	649
	4.0	176	254	326	395	460	522	581	637	692

Downhill 2%	1.5	108	163	219	275	331	387	443	500	557
	2.0	131	195	258	321	382	444	505	565	626
	2.5	148	218	288	355	422	488	553	617	681
	3.0	161	238	312	384	455	524	593	661	727
	3.5	173	254	332	409	483	557	628	698	768
	4.0	183	269	351	431	509	585	659	733	805

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 1.00 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	68	93	113	131	145	158	167	176	184
	2.0	90	125	156	183	207	228	247	265	280
	2.5	105	147	185	219	249	277	302	326	347
	3.0	116	164	208	247	282	315	345	373	399
	3.5	126	179	227	270	310	347	381	412	442
	4.0	135	192	243	291	334	375	412	447	480

Flat terrain	1.5	76	109	140	169	196	222	246	270	293
	2.0	96	138	177	214	249	282	314	345	374
	2.5	110	158	204	246	286	325	362	397	431
	3.0	121	175	225	272	317	359	400	439	477
	3.5	131	189	243	294	342	388	432	474	515
	4.0	139	201	258	313	364	414	461	506	549

Downhill 2%	1.5	83	125	166	208	248	290	330	372	412
	2.0	102	151	199	246	292	337	382	428	472
	2.5	115	170	223	274	325	374	422	471	518
	3.0	126	185	242	298	352	404	456	507	556
	3.5	135	198	259	318	374	430	484	537	590
	4.0	144	210	274	336	395	453	510	565	620

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 1.60 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	51	71	88	103	116	127	138	147	155
	2.0	67	95	119	141	160	179	195	210	224
	2.5	78	110	140	166	191	214	234	254	272
	3.0	86	123	156	187	214	241	265	288	309
	3.5	93	133	170	204	235	263	290	316	340
	4.0	100	143	182	218	251	284	313	341	367

Flat terrain	1.5	56	80	103	124	144	163	182	200	216
	2.0	70	101	130	158	184	208	231	254	276
	2.5	81	116	150	181	211	239	266	293	318
	3.0	89	128	165	200	233	265	294	324	352
	3.5	96	139	178	216	252	286	318	350	380
	4.0	102	147	190	230	268	305	339	373	405

Downhill 2%	1.5	60	89	117	145	173	200	228	255	282
	2.0	74	108	142	175	206	238	269	299	329
	2.5	84	122	160	197	232	266	300	333	365
	3.0	92	134	175	214	252	289	325	360	395
	3.5	98	144	187	229	269	309	346	384	421
	4.0	104	152	198	242	285	326	366	405	444

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 2.30 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	41	58	72	85	97	106	116	124	132
	2.0	53	76	96	114	130	146	160	174	186
	2.5	62	88	112	134	154	173	190	207	222
	3.0	68	98	124	150	172	194	214	233	251
	3.5	74	106	135	163	188	211	234	256	276
	4.0	79	113	145	174	202	228	251	275	297

Flat terrain	1.5	44	63	81	98	114	130	144	158	171
	2.0	55	80	103	125	145	165	183	201	218
	2.5	64	92	118	143	167	189	210	231	251
	3.0	70	101	130	158	184	209	233	256	278
	3.5	76	109	141	171	199	226	252	276	301
	4.0	80	116	150	182	212	241	268	294	320

Downhill 2%	1.5	46	68	90	111	132	153	173	193	212
	2.0	57	84	110	135	160	183	206	230	252
	2.5	65	95	124	153	179	206	231	257	281
	3.0	72	105	136	167	196	224	252	279	305
	3.5	77	113	146	179	209	240	270	298	326
	4.0	82	119	155	189	222	254	285	315	344

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition



## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 3.50 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	32	45	56	67	77	85	94	101	108
	2.0	41	58	74	89	102	114	126	137	147
	2.5	47	68	86	104	119	134	149	162	175
	3.0	52	75	96	115	133	151	166	182	196
	3.5	56	81	104	125	145	164	182	198	215
	4.0	60	86	111	134	155	175	194	213	230

Flat terrain	1.5	33	48	62	75	87	99	110	121	131
	2.0	42	61	78	95	110	125	139	153	166
	2.5	48	70	90	109	127	144	161	176	192
	3.0	53	77	99	120	140	159	178	195	212
	3.5	57	83	107	130	151	172	192	211	229
	4.0	61	88	114	138	161	183	204	224	244

Downhill 2%	1.5	35	51	67	82	97	112	126	140	154
	2.0	43	63	82	101	119	136	153	169	186
	2.5	49	72	94	114	134	153	173	191	209
	3.0	54	79	102	125	147	168	188	208	228
	3.5	58	85	110	134	158	180	202	223	244
	4.0	62	90	117	143	167	191	214	236	258

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 0.70 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	130	162	184	199	209	217	223	228	231
	2.0	182	238	280	313	340	361	378	393	406
	2.5	218	289	346	393	432	466	494	518	539
	3.0	246	329	398	456	505	548	586	618	648
	3.5	269	363	442	509	566	617	662	703	739
	4.0	289	392	479	554	620	678	730	777	819

Flat terrain	1.5	168	233	292	347	397	445	489	532	573
	2.0	213	297	373	443	507	568	626	681	734
	2.5	245	343	430	511	586	656	722	787	848
	3.0	271	379	476	565	648	727	801	871	939
	3.5	293	409	514	611	701	786	866	943	1017
	4.0	312	436	548	652	748	839	925	1006	1085

Downhill 2%	1.5	207	309	412	514	616	718	817	905	990
	2.0	245	359	471	581	689	796	900	995	1087
	2.5	273	397	517	634	748	860	969	1068	1166
	3.0	296	429	556	678	797	914	1027	1132	1235
	3.5	316	456	591	717	841	962	1079	1189	1295
	4.0	334	480	619	752	880	1005	1126	1239	1350

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition  
Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 1.00 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	109	140	162	178	190	200	208	214	219
	2.0	149	198	236	268	295	316	335	352	366
	2.5	177	238	288	331	367	398	426	451	473
	3.0	199	269	328	380	424	463	498	530	558
	3.5	217	296	362	420	472	517	558	596	630
	4.0	233	318	392	456	512	564	610	653	692

Flat terrain	1.5	133	185	232	276	316	353	389	423	456
	2.0	169	236	296	352	403	452	498	542	583
	2.5	194	272	341	406	465	522	574	626	674
	3.0	215	300	378	449	515	577	636	693	747
	3.5	232	325	408	485	557	624	689	750	809
	4.0	247	346	435	518	594	666	734	800	863

Downhill 2%	1.5	157	233	308	382	455	528	601	673	745
	2.0	189	275	358	439	518	596	674	750	826
	2.5	212	306	396	483	568	650	731	812	891
	3.0	230	332	428	520	609	696	781	864	947
	3.5	247	354	455	552	645	736	824	911	996
	4.0	261	374	480	581	677	771	863	953	1041

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition  
Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 1.60 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	85	111	132	148	161	173	182	190	196
	2.0	114	153	186	214	237	258	277	293	308
	2.5	134	182	222	258	289	317	342	365	386
	3.0	149	204	252	293	330	363	394	421	447
	3.5	162	223	276	323	364	402	437	469	499
	4.0	174	240	297	348	394	436	474	510	544

Flat terrain	1.5	98	137	171	203	233	261	287	313	337
	2.0	124	174	218	260	298	333	368	401	431
	2.5	143	200	252	299	343	385	425	463	498
	3.0	158	221	278	331	380	426	470	512	552
	3.5	170	239	301	358	411	461	509	554	598
	4.0	181	255	321	382	439	492	542	591	638

Downhill 2%	1.5	111	163	212	262	310	357	404	451	498
	2.0	135	195	252	307	361	412	464	515	564
	2.5	152	219	281	341	399	455	510	564	617
	3.0	166	238	306	370	431	491	549	606	661
	3.5	178	255	326	394	459	522	582	642	700
	4.0	189	270	345	416	484	550	613	674	735

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition



## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 2.30 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	69	92	110	126	139	150	159	167	175
	2.0	91	124	152	176	197	216	233	248	263
	2.5	107	146	181	211	238	262	284	304	323
	3.0	119	164	203	238	269	298	324	348	371
	3.5	129	179	222	261	296	328	358	385	411
	4.0	138	192	238	281	319	354	386	417	446

Flat terrain	1.5	77	108	136	161	184	207	228	248	267
	2.0	98	137	173	205	235	264	291	317	342
	2.5	113	158	199	237	272	305	336	366	395
	3.0	124	175	220	262	301	337	372	405	437
	3.5	134	189	238	283	325	365	402	439	473
	4.0	143	201	254	302	347	389	430	468	505

Downhill 2%	1.5	85	124	161	197	232	267	302	335	369
	2.0	105	150	194	235	275	314	351	389	425
	2.5	119	170	217	263	307	349	390	430	469
	3.0	130	185	237	286	332	378	422	464	506
	3.5	139	199	254	306	355	403	449	494	537
	4.0	148	210	268	323	375	425	474	520	566

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ CNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 3.50 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	1.5	54	73	89	102	114	124	133	141	149
	2.0	71	97	120	140	157	174	188	202	214
	2.5	82	114	141	166	187	207	226	243	259
	3.0	92	127	158	186	211	235	256	276	295
	3.5	99	138	172	203	231	257	281	303	325
	4.0	106	148	184	218	248	277	302	328	351

Flat terrain	1.5	59	82	103	123	141	158	174	189	204
	2.0	75	104	132	157	179	202	222	242	261
	2.5	86	120	152	181	207	232	257	280	302
	3.0	95	133	168	200	229	258	284	310	334
	3.5	102	144	181	216	248	279	307	335	361
	4.0	109	153	193	230	265	297	328	357	386

Downhill 2%	1.5	63	92	118	144	169	193	217	240	264
	2.0	78	112	144	174	202	230	258	284	310
	2.5	89	127	162	196	227	258	288	317	345
	3.0	98	139	177	214	248	281	313	344	374
	3.5	105	149	190	229	265	300	334	367	399
	4.0	111	158	202	243	281	318	354	388	421

Minimum considered pressure 1.0 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 0.85 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	75	101	123	141	155	167	178	186	194
	2.5	99	137	171	200	225	247	267	285	301
	3.0	116	162	203	240	272	302	329	353	375
	3.5	129	182	229	271	310	344	377	407	434
	4.0	140	198	250	298	341	380	417	451	483
Flat terrain	2.0	84	121	155	187	217	246	274	301	326
	2.5	107	153	197	238	277	314	349	383	415
	3.0	122	176	226	274	319	361	402	441	479
	3.5	135	194	250	303	352	399	444	488	530
	4.0	146	210	270	327	380	431	480	527	573
Downhill 2%	2.0	94	141	188	236	283	330	378	425	472
	2.5	114	170	224	277	330	382	434	485	536
	3.0	129	191	250	309	365	421	477	532	586
	3.5	141	207	272	334	395	454	514	572	628
	4.0	151	222	290	356	421	483	545	606	665

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 1.25 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	60	82	101	117	131	143	154	162	170
	2.5	78	110	137	162	184	204	222	238	253
	3.0	91	128	162	192	220	245	268	290	310
	3.5	101	143	181	216	248	277	305	330	354
	4.0	109	156	198	236	272	305	335	365	391
Flat terrain	2.0	65	94	121	146	169	192	214	234	254
	2.5	83	119	153	185	215	244	272	298	324
	3.0	95	137	176	213	248	281	313	344	373
	3.5	105	151	194	235	274	311	346	380	413
	4.0	113	163	210	254	296	335	374	410	446
Downhill 2%	2.0	71	106	140	175	209	243	277	311	344
	2.5	87	129	169	209	247	286	323	360	397
	3.0	99	146	190	234	276	318	358	399	438
	3.5	108	159	207	254	300	344	388	430	472
	4.0	116	170	222	272	320	367	413	458	502

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 2.00 l/h

	Inlet pressure (bar)	Distance between drippers (meter)								
		0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	45	63	78	92	104	114	124	133	141
	2.5	58	82	104	124	142	158	173	187	200
	3.0	67	96	122	146	167	188	206	224	240
	3.5	75	107	136	163	188	211	233	253	272
	4.0	81	116	148	177	205	230	254	277	299
Flat terrain	2.0	48	69	89	107	125	141	158	173	187
	2.5	61	88	112	136	158	180	200	220	239
	3.0	70	101	130	157	182	207	230	253	275
	3.5	77	111	143	173	202	229	255	280	304
	4.0	83	120	154	187	218	247	275	302	329
Downhill 2%	2.0	51	76	100	123	146	169	192	214	236
	2.5	63	93	121	149	176	202	228	254	279
	3.0	72	105	137	168	198	227	255	284	311
	3.5	79	115	150	184	215	247	278	308	337
	4.0	85	124	161	197	231	264	297	329	359

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 2.90 l/h

	Inlet pressure (bar)	Distance between drippers (meter)								
		0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	36	50	63	75	85	95	103	111	118
	2.5	46	65	83	99	114	127	141	152	164
	3.0	53	76	97	116	134	151	166	181	195
	3.5	59	84	108	130	149	169	186	203	220
	4.0	64	92	117	141	163	184	203	222	240
Flat terrain	2.0	38	54	70	84	98	111	124	136	147
	2.5	48	69	88	107	125	141	158	173	188
	3.0	55	79	102	123	143	162	182	199	216
	3.5	60	87	112	136	158	180	200	221	239
	4.0	65	94	121	147	171	194	217	238	259
Downhill 2%	2.0	40	58	76	94	111	128	145	161	178
	2.5	49	72	94	115	135	155	174	194	213
	3.0	56	82	106	130	153	175	197	218	238
	3.5	61	89	116	142	167	191	214	237	259
	4.0	66	96	125	153	179	204	230	254	277

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 16010/16012 • ID 14.2 mm • Kd 1.3 • Flow rate 4.40 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	28	39	49	59	67	75	82	89	96
	2.5	35	50	64	77	89	100	110	120	129
	3.0	41	58	74	90	104	117	130	141	153
	3.5	45	65	83	100	116	131	145	158	171
	4.0	49	70	90	108	125	142	158	173	187
Flat terrain	2.0	29	41	53	64	75	85	94	104	113
	2.5	36	52	67	82	95	108	120	132	144
	3.0	41	60	77	94	109	124	138	152	165
	3.5	46	66	85	104	121	137	153	168	183
	4.0	49	71	92	112	130	148	165	182	198
Downhill 2%	2.0	30	44	57	70	83	95	107	119	130
	2.5	37	54	70	86	101	116	130	144	158
	3.0	42	62	80	98	115	131	147	163	178
	3.5	46	68	88	107	125	144	161	178	194
	4.0	50	73	94	115	135	154	173	191	208

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 0.85 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	118	150	172	188	199	209	215	221	225
	2.5	164	215	256	289	315	337	355	372	385
	3.0	195	260	314	359	396	428	457	482	504
	3.5	219	296	359	413	460	501	538	570	599
	4.0	239	325	397	459	513	561	605	644	679
Flat terrain	2.0	148	206	258	306	350	392	432	470	506
	2.5	188	262	329	391	448	501	552	601	648
	3.0	216	302	379	451	517	579	638	694	748
	3.5	239	334	420	499	572	641	706	769	829
	4.0	258	361	454	539	619	694	765	833	898
Downhill 2%	2.0	178	265	351	437	521	607	691	776	860
	2.5	212	310	405	498	589	679	769	857	945
	3.0	238	344	447	546	643	738	831	923	1015
	3.5	258	373	481	586	688	787	885	980	1075
	4.0	276	397	512	621	727	831	932	1031	1129

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition  
 Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 1.25 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	97	126	147	164	177	188	196	203	209
	2.5	131	176	211	242	266	288	307	324	338
	3.0	155	210	255	295	329	358	386	410	431
	3.5	174	236	290	336	377	414	447	477	504
	4.0	189	259	319	371	418	460	498	533	566
Flat terrain	2.0	115	160	201	239	273	306	337	366	395
	2.5	146	204	256	304	349	391	431	469	506
	3.0	168	235	295	351	403	452	498	542	584
	3.5	185	260	327	389	446	500	551	600	647
	4.0	200	281	353	420	482	541	597	650	701
Downhill 2%	2.0	133	196	258	318	378	438	497	555	614
	2.5	161	233	302	370	435	500	563	626	688
	3.0	181	261	336	409	479	548	615	681	747
	3.5	197	283	364	442	516	589	659	729	797
	4.0	211	303	388	470	548	624	698	770	841

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition  
 Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

### Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 2.00 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	75	99	118	135	148	159	168	176	183
	2.5	99	135	164	190	212	232	250	266	280
	3.0	117	159	196	228	257	282	306	327	347
	3.5	130	179	221	258	292	322	350	375	399
	4.0	141	195	242	283	320	355	386	416	443
Flat terrain	2.0	85	118	148	176	202	226	249	271	292
	2.5	107	150	189	225	257	289	318	347	374
	3.0	124	173	218	259	297	333	368	401	432
	3.5	136	191	241	287	329	369	407	444	478
	4.0	147	207	260	310	356	400	441	480	518
Downhill 2%	2.0	94	137	179	220	259	298	337	375	413
	2.5	115	166	214	260	305	348	390	433	474
	3.0	131	187	240	291	339	386	432	477	521
	3.5	143	204	261	316	367	418	466	514	560
	4.0	153	219	279	337	392	445	496	546	595

Minimum considered pressure 1.5 bar. Max. working pressure according the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 2.90 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	60	81	98	113	125	135	145	153	160
	2.5	79	108	133	155	175	192	207	222	235
	3.0	93	128	158	185	209	230	250	269	287
	3.5	103	143	177	208	236	261	285	307	327
	4.0	112	155	193	227	258	287	314	338	361
Flat terrain	2.0	66	93	116	139	159	178	196	213	230
	2.5	84	118	148	177	203	228	251	274	295
	3.0	97	136	171	204	234	263	290	315	340
	3.5	107	150	189	226	259	291	321	349	377
	4.0	116	162	204	244	280	314	347	378	408
Downhill 2%	2.0	72	105	136	166	194	223	251	278	306
	2.5	89	128	164	199	232	264	296	327	357
	3.0	101	144	185	223	260	295	330	363	395
	3.5	111	158	202	243	283	321	357	392	428
	4.0	119	170	216	261	302	342	381	419	455

Minimum considered pressure 1.5 bar. Max. working pressure according to the dripline wall thickness definition

## Max. lateral length (meter) at different inlet pressure and different slopes

UniGray™ HCNL 20010/20012 • ID 17.5 mm • Kd 0.4 • Flow rate 4.40 l/h

	Distance between drippers (meter)									
	Inlet pressure (bar)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Uphill 2%	2.0	47	64	78	91	101	111	119	127	134
	2.5	61	84	104	123	139	153	166	179	190
	3.0	71	99	123	145	164	182	198	214	229
	3.5	79	110	137	162	184	205	224	242	259
	4.0	86	119	149	177	201	224	246	266	285
Flat terrain	2.0	51	71	89	106	121	137	150	164	176
	2.5	64	90	113	135	155	174	192	209	225
	3.0	74	104	131	156	179	201	222	241	260
	3.5	81	115	144	172	198	222	245	267	288
	4.0	88	124	156	186	214	240	266	289	312
Downhill 2%	2.0	54	78	100	122	142	162	182	202	221
	2.5	67	96	122	148	172	195	218	240	262
	3.0	76	109	138	167	194	220	245	269	293
	3.5	84	119	152	183	212	239	266	293	318
	4.0	90	128	163	196	227	257	286	313	340

Minimum considered pressure 1.5 bar. Max. working pressure according to the dripline wall thickness definition