

Leach Line™ X

Heap leaching dripline.
Integral non-pressure-compensated.
Superior clogging resistance.

→ 16009 - 16010 - 16012 - 20010 - 20012



High clogging
resistance



Self-cleaning
labyrinth



Anti-migration
mechanism (optional)

/ Benefits & Features

- **High clogging resistance** Even with challenging solution quality, with self-cleaning labyrinth that flushes debris throughout operation.
- **Wide filtration area** Ensures optimal performance even under harsh solution conditions, preventing the entrance of sediments into the drippers.
- **Wide water passages** TurboNet™ labyrinth ensures wide solution passages, large deep and wide cross-section that improves clogging resistance.
- **Anti-migration clip (smart clip)** Prevents solution migration on uneven surfaces and slopes.
Economical - saves labor. Pre-installed on the dripline during production (optional).

/ Specifications

- ✓ Maximum operating pressure according to driplines diameters and wall thickness. See tables below.
- ✓ Recommended filtration: 200 micron / 80 mesh. Filtration method selected based on the kind and concentration of dirt particles contained in the solution. Wherever sand exceeding 2 ppm exists in the solution, a Hydrocyclone shall be installed before the main filter. Where sand/silt/clay solids exceed 100 ppm, pre treatment shall be applied following Netafim expert instructions.
- ✓ TurboNet™ labyrinth with large water passage.
- ✓ Weldable into thick wall driplines (0.90, 1.00, 1.20 mm).
- ✓ Injected dripper, very low CV.
- ✓ High UV resistance. Resistant to chemicals used in heap leaching mines.
- ✓ Meets ISO 9261 Standards.

→ Drippers technical data

16009, 16010, 20010 - 0.9 and 1.0 mm wall thickness driplines

| Flow rate* (l/h) | Max. working pressure (bar)** | Water passages dimensions width-depth-length (mm) | Filtration area (mm ²) | Constant K | Exponent X | Recommended filtration (micron)/(mesh) |
|------------------|-------------------------------|---|------------------------------------|------------|------------|--|
| 1.00 | 3.0 / 3.5 | 0.60 x 0.80 x 75 | 70 | 0.348 | 0.46 | 200 / 80 |
| 1.50 | | 0.73 x 0.90 x 75 | 70 | 0.520 | 0.46 | 200 / 80 |
| 2.00 | | 0.76 x 1.09 x 75 | 70 | 0.693 | 0.46 | 200 / 80 |
| 4.00 | | 1.06 x 1.40 x 75 | 76 | 1.387 | 0.46 | 200 / 80 |
| 8.00 | | 1.68 x 1.40 x 37 | 76 | 2.774 | 0.46 | 200 / 80 |

* Flow rate at 1.0 bar pressure ** According to dripline wall thickness

16012, 20012 - 1.2 mm wall thickness driplines

| Flow rate* (l/h) | Max. working pressure (bar) | Water passages dimensions width-depth-length (mm) | Filtration area (mm ²) | Constant K | Exponent X | Recommended filtration (micron)/(mesh) |
|------------------|-----------------------------|---|------------------------------------|------------|------------|--|
| 1.05 | 4.0 | 0.60 x 0.80 x 75 | 70 | 0.364 | 0.46 | 200 / 80 |
| 1.50 | | 0.73 x 0.90 x 75 | 70 | 0.520 | 0.46 | 200 / 80 |
| 2.10 | | 0.76 x 1.09 x 75 | 70 | 0.728 | 0.46 | 200 / 80 |
| 4.20 | | 1.06 x 1.40 x 75 | 76 | 1.456 | 0.46 | 200 / 80 |
| 8.40 | | 1.68 x 1.40 x 37 | 76 | 2.913 | 0.46 | 200 / 80 |

* Flow rate at 1.0 bar pressure

→ Driplines technical data

| Model | Inside diameter (mm) | Wall thickness (mm) | Outside diameter (mm) | Max. working pressure (bar) | Max. flushing pressure (bar) | Kd |
|-------|----------------------|---------------------|-----------------------|-----------------------------|------------------------------|------|
| 16009 | 14.20 | 0.90 | 16.00 | 3.0 | 3.9 | 0.40 |
| 16010 | 14.20 | 1.00 | 16.20 | 3.5 | 4.6 | 0.40 |
| 16012 | 14.20 | 1.20 | 16.60 | 4.0 | 5.2 | 0.40 |
| 20010 | 17.50 | 1.00 | 19.50 | 3.5 | 4.6 | 0.10 |
| 20012 | 17.50 | 1.20 | 19.90 | 4.0 | 5.2 | 0.10 |

→ Driplines packaging data (on bundles coils)

| Model | Wall thickness (mm) | Distance between drippers (m) | Coil length (m) | Average* coil weight (kg) | Coils in a 40 feet container (units) | Total in a 40 feet container (m) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------------------|----------------------------------|
| 16009 | 0.90 | 0.15 to 1.00 | 500 | 20.7 | 330 | 165000 |
| 16010 | 1.00 | 0.15 to 1.00 | 500 | 23.0 | 330 | 165000 |
| 16012 | 1.20 | 0.15 to 1.00 | 400 | 22.3 | 352 | 140800 |
| 20010 | 1.00 | 0.15 to 1.00 | 300 | 16.7 | 330 | 99000 |
| 20012 | 1.20 | 0.15 to 1.00 | 300 | 20.2 | 330 | 99000 |

* Calculated weight average. For further details see "Average Coil Weight Disclaimer".

→ Driplines packaging data (on bundles coils) with assembly anti-migration clips

| Model | Wall thickness (mm) | Distance between drippers (m) | Coil length (m) | Average* coil weight (kg) | Coils in a 40 feet container (units) | Total in a 40 feet container (m) |
|-------|---------------------|-------------------------------|-----------------|---------------------------|--------------------------------------|----------------------------------|
| 16009 | 0.90 | 0.15 to 1.00 | 300 | 13.0 | 330 | 99000 |
| 16010 | 1.00 | 0.15 to 1.00 | 300 | 15.0 | 330 | 99000 |
| 16012 | 1.20 | 0.15 to 1.00 | 300 | 17.9 | 330 | 99000 |
| 20010 | 1.00 | 0.15 to 1.00 | 300 | 18.0 | 330 | 99000 |
| 20012 | 1.20 | 0.15 to 1.00 | 300 | 21.5 | 330 | 99000 |

* Calculated weight average. For further details see "Average Coil Weight Disclaimer".

/ Drippers flow rate vs working pressure

In order to calculate the right flow rate of each dripper, under different working pressures, we use the following formula:

$$Q = K * P^X$$

Where:

Q = Dripper flow rate (liters/hour)

K = Constant (each dripper has his singular constant and must be defined by the dripper producer)

P = Real working pressure (meter)

X = Exponent (each dripper has its singular exponent and must be declared and defined by the dripper producer)

*ISO 9261 require from the manufacturer to declare the constant K and dripper exponent

Non-pressure-compensated drippers provide flow adequate to the pressure it is exposed to, according to the formula presented above. In order to simplify the calculations and understandings of the linkage between the flow and the pressure, a table with the flow rates at different working pressures is presented here for each of the drippers presented in this document.

Flow rate (l/h) vs pressure (bar)

16009/16010/20010 - 0.9 and 1.0 mm wall thickness driplines

| Flow rate* (l/h) | Pressure (bar) | | | | | | | | |
|---------------------|----------------|------|------|------|------|------|-------|-------|-------|
| | 0.2 | 0.4 | 0.6 | 0.8 | 1.0 | 1.5 | 2.0 | 2.5 | 3.0 |
| 1.00 | 0.48 | 0.66 | 0.79 | 0.90 | 1.00 | 1.21 | 1.38 | 1.53 | 1.66 |
| 1.50 | 0.72 | 0.98 | 1.19 | 1.35 | 1.50 | 1.81 | 2.06 | 2.29 | 2.49 |
| 2.00 | 0.95 | 1.31 | 1.58 | 1.80 | 2.00 | 2.41 | 2.75 | 3.05 | 3.31 |
| 3.00 | 1.43 | 1.97 | 2.37 | 2.71 | 3.00 | 3.61 | 4.13 | 4.57 | 4.97 |
| 4.00 | 1.91 | 2.62 | 3.16 | 3.61 | 4.00 | 4.82 | 5.50 | 6.10 | 6.63 |
| 8.00 | 3.81 | 5.25 | 6.32 | 7.22 | 8.00 | 9.64 | 11.00 | 12.19 | 13.26 |

*Flow rate at 1.0 bar pressure

Flow rate (l/h) vs pressure (bar)

16012/20012 - 1.2 mm wall thickness driplines

| fFlow rate* (l/h) | Pressure (bar) | | | | | | | | |
|----------------------|----------------|------|------|------|------|-------|-------|-------|-------|
| | 0.2 | 0.4 | 0.6 | 0.8 | 1.0 | 1.5 | 2.0 | 2.5 | 3.0 |
| 1.05 | 0.50 | 0.69 | 0.83 | 0.95 | 1.05 | 1.27 | 1.44 | 1.60 | 1.74 |
| 1.60 | 0.76 | 1.05 | 1.26 | 1.44 | 1.60 | 1.93 | 2.20 | 2.44 | 2.65 |
| 2.10 | 1.00 | 1.38 | 1.66 | 1.89 | 2.10 | 2.53 | 2.89 | 3.20 | 3.48 |
| 3.15 | 1.50 | 2.07 | 2.49 | 2.84 | 3.15 | 3.80 | 4.33 | 4.80 | 5.22 |
| 4.20 | 2.00 | 2.75 | 3.32 | 3.79 | 4.20 | 5.06 | 5.77 | 6.40 | 6.96 |
| 8.40 | 4.01 | 5.51 | 6.64 | 7.58 | 8.40 | 10.12 | 11.55 | 12.80 | 13.92 |

*Flow rate at 1.0 bar pressure

/ Max. lateral length

Flow Variation (FV) expresses the flow variation between the dripper “sensing” the highest pressure and the one “sensing” the lowest pressure in an irrigation block (zone).

These drippers will not always be the first and last drippers on the dripline.

$$FV \% = (Q_{\max} - Q_{\min}) / Q_{\max} * 100$$

*International standards define 10% flow variation to be considered as uniform irrigation.

In order to calculate the maximum run lengths that can be planned for specific dripline (considering all the hydraulic factors influencing the flow within the same dripline), we use a calculation software that was developed by Netafim™ based on Darcy-Waisbach formulas + years of design experience and cooperation with academic institutes.

All the tables presented in this document are for initial reference only; the exact run length of the driplines is obtained from design software that considers various hydraulic factors in the entire system.

There might be small variance between the different software's in the market due to the calculation method and assumptions each software is using. For an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

Non-pressure-compensated drippers of Netafim™ will provide different flow according to the real working pressure, therefore, the influencing factors will be: the pressure that each dripper in the dripline is exposed to, and the allowed flow variation the dripline is designed to, which in most cases is defined as 10% difference in flow, according to the international standards, and / or any other limitation that the customer / planner will prefer to design while considering the crop needs and area topography.

The following tables are only displayed at one inlet pressure for each dripline, since in non-pressure-compensated drippers the flow varies according to the pressure. There might be differences in run lengths with different inlet pressures; however for an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16009/16010 • ID 14.2 mm • Kd 0.40 • Flow rate 1.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 65 | 83 | 96 | 107 | 115 | 122 | 126 | 131 | 135 |
| | 1% | 71 | 95 | 114 | 131 | 145 | 158 | 169 | 179 | 188 |
| Flat terrain | 0 | 78 | 108 | 134 | 159 | 181 | 202 | 222 | 241 | 259 |
| Downhill | -1% | 83 | 118 | 151 | 182 | 212 | 242 | 270 | 298 | 326 |
| | -2% | 89 | 130 | 169 | 208 | 246 | 284 | 323 | 361 | 400 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16009/16010 • ID 14.2 mm • Kd 0.40 • Flow rate 1.50 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 52 | 68 | 80 | 91 | 99 | 106 | 112 | 117 | 121 |
| | 1% | 56 | 75 | 92 | 106 | 118 | 130 | 139 | 149 | 157 |
| Flat terrain | 0 | 60 | 83 | 104 | 123 | 140 | 156 | 171 | 186 | 201 |
| Downhill | -1% | 63 | 89 | 113 | 136 | 158 | 179 | 200 | 220 | 240 |
| | -2% | 66 | 96 | 124 | 151 | 178 | 204 | 230 | 257 | 282 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16009/16010 • ID 14.2 mm • Kd 0.40 • Flow rate 2.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 44 | 59 | 70 | 80 | 88 | 95 | 101 | 106 | 110 |
| | 1% | 47 | 64 | 78 | 90 | 101 | 111 | 121 | 130 | 136 |
| Flat terrain | 0 | 50 | 69 | 86 | 102 | 116 | 130 | 143 | 155 | 167 |
| Downhill | -1% | 52 | 73 | 93 | 111 | 128 | 146 | 162 | 178 | 194 |
| | -2% | 54 | 78 | 100 | 122 | 142 | 163 | 183 | 203 | 223 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16009/16010 • ID 14.2 mm • Kd 0.40 • Flow rate 4.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 30 | 40 | 48 | 56 | 63 | 69 | 74 | 78 | 83 |
| | 1% | 31 | 42 | 52 | 61 | 68 | 76 | 82 | 88 | 94 |
| Flat terrain | 0 | 32 | 44 | 55 | 66 | 75 | 84 | 91 | 100 | 107 |
| Downhill | -1% | 32 | 46 | 58 | 69 | 79 | 90 | 99 | 109 | 118 |
| | -2% | 33 | 47 | 60 | 73 | 85 | 97 | 108 | 119 | 129 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16009/16010 • ID 14.2 mm • Kd 0.40 • Flow rate 8.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 19 | 26 | 33 | 38 | 43 | 48 | 52 | 58 | 59 |
| | 1% | 20 | 27 | 34 | 40 | 46 | 50 | 55 | 60 | 64 |
| Flat terrain | 0 | 20 | 28 | 36 | 42 | 48 | 54 | 59 | 65 | 70 |
| Downhill | -1% | 21 | 29 | 36 | 43 | 50 | 56 | 62 | 68 | 73 |
| | -2% | 21 | 29 | 38 | 45 | 52 | 59 | 66 | 72 | 78 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16012 • ID 14.2 mm • Kd 0.40 • Flow rate 1.05 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 63 | 81 | 94 | 105 | 113 | 120 | 126 | 130 | 134 |
| | 1% | 69 | 93 | 112 | 128 | 142 | 155 | 166 | 176 | 185 |
| Flat terrain | 0 | 76 | 105 | 130 | 154 | 176 | 196 | 215 | 234 | 252 |
| Downhill | -1% | 81 | 114 | 146 | 176 | 205 | 233 | 261 | 288 | 314 |
| | -2% | 86 | 125 | 163 | 201 | 237 | 274 | 310 | 347 | 384 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16012 • ID 14.2 mm • Kd 0.40 • Flow rate 1.60 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 50 | 66 | 78 | 89 | 97 | 103 | 110 | 114 | 119 |
| | 1% | 54 | 73 | 88 | 103 | 114 | 125 | 135 | 144 | 152 |
| Flat terrain | 0 | 58 | 80 | 100 | 118 | 134 | 150 | 165 | 179 | 193 |
| Downhill | -1% | 60 | 85 | 108 | 130 | 151 | 171 | 190 | 210 | 228 |
| | -2% | 63 | 91 | 118 | 144 | 169 | 194 | 218 | 243 | 267 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16012 • ID 14.2 mm • Kd 0.40 • Flow rate 2.10 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 43 | 57 | 68 | 78 | 86 | 92 | 99 | 104 | 108 |
| | 1% | 46 | 62 | 76 | 88 | 99 | 109 | 118 | 125 | 133 |
| Flat terrain | 0 | 48 | 67 | 84 | 99 | 113 | 126 | 138 | 150 | 162 |
| Downhill | -1% | 50 | 71 | 90 | 108 | 124 | 141 | 156 | 172 | 187 |
| | -2% | 52 | 75 | 96 | 117 | 137 | 157 | 176 | 195 | 214 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16012 • ID 14.2 mm • Kd 0.40 • Flow rate 4.20 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 29 | 39 | 47 | 55 | 61 | 67 | 72 | 77 | 81 |
| | 1% | 30 | 41 | 50 | 59 | 67 | 74 | 80 | 86 | 92 |
| Flat terrain | 0 | 31 | 43 | 54 | 64 | 73 | 81 | 89 | 96 | 104 |
| Downhill | -1% | 31 | 44 | 56 | 67 | 77 | 87 | 96 | 105 | 114 |
| | -2% | 32 | 46 | 58 | 71 | 82 | 93 | 104 | 114 | 125 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 16012 • ID 14.2 mm • Kd 0.40 • Flow rate 8.40 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 19 | 26 | 32 | 37 | 42 | 46 | 60 | 54 | 58 |
| | 1% | 19 | 27 | 33 | 39 | 44 | 49 | 54 | 59 | 63 |
| Flat terrain | 0 | 20 | 27 | 34 | 41 | 47 | 53 | 58 | 63 | 68 |
| Downhill | -1% | 20 | 28 | 35 | 42 | 48 | 54 | 60 | 66 | 71 |
| | -2% | 20 | 29 | 36 | 44 | 50 | 57 | 63 | 69 | 75 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20010 • ID 17.5 mm • Kd 0.140 • Flow rate 1.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 93 | 111 | 123 | 132 | 137 | 141 | 145 | 148 | 150 |
| | 1% | 110 | 139 | 161 | 179 | 195 | 207 | 218 | 229 | 236 |
| Flat terrain | 0 | 128 | 170 | 208 | 243 | 274 | 304 | 332 | 359 | 384 |
| Downhill | -1% | 143 | 199 | 251 | 301 | 349 | 397 | 444 | 491 | 537 |
| | -2% | 160 | 229 | 298 | 366 | 434 | 503 | 572 | 641 | 710 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20010 • ID 17.5 mm • Kd 0.140 • Flow rate 1.50 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 78 | 95 | 108 | 117 | 124 | 130 | 134 | 138 | 141 |
| | 1% | 88 | 113 | 132 | 149 | 163 | 176 | 186 | 196 | 205 |
| Flat terrain | 0 | 99 | 132 | 161 | 188 | 212 | 235 | 257 | 278 | 298 |
| Downhill | -1% | 108 | 148 | 186 | 222 | 256 | 290 | 322 | 356 | 387 |
| | -2% | 117 | 166 | 213 | 260 | 305 | 351 | 397 | 443 | 489 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20010 • ID 17.5 mm • Kd 0.140 • Flow rate 2.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 67 | 84 | 96 | 106 | 113 | 119 | 125 | 130 | 133 |
| | 1% | 75 | 96 | 114 | 129 | 142 | 154 | 164 | 174 | 182 |
| Flat terrain | 0 | 82 | 110 | 134 | 156 | 177 | 195 | 214 | 231 | 248 |
| Downhill | -1% | 88 | 121 | 151 | 180 | 207 | 233 | 259 | 284 | 309 |
| | -2% | 95 | 133 | 170 | 205 | 240 | 274 | 309 | 343 | 377 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20010 • ID 17.5 mm • Kd 0.140 • Flow rate 4.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 46 | 59 | 70 | 79 | 86 | 92 | 98 | 103 | 107 |
| | 1% | 49 | 65 | 78 | 89 | 99 | 109 | 117 | 124 | 131 |
| Flat terrain | 0 | 53 | 71 | 86 | 101 | 113 | 126 | 138 | 149 | 159 |
| Downhill | -1% | 55 | 75 | 93 | 110 | 125 | 141 | 155 | 170 | 184 |
| | -2% | 58 | 80 | 100 | 120 | 139 | 157 | 175 | 194 | 211 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20010 • ID 17.5 mm • Kd 0.140 • Flow rate 8.00 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 31 | 41 | 48 | 56 | 62 | 67 | 71 | 76 | 80 |
| | 1% | 32 | 43 | 52 | 60 | 67 | 74 | 80 | 86 | 91 |
| Flat terrain | 0 | 34 | 45 | 56 | 65 | 73 | 81 | 89 | 95 | 103 |
| Downhill | -1% | 35 | 47 | 58 | 68 | 78 | 87 | 96 | 104 | 113 |
| | -2% | 36 | 49 | 61 | 73 | 83 | 94 | 104 | 113 | 123 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20012 • ID 17.5 mm • Kd 0.10 • Flow rate 1.05 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 91 | 109 | 121 | 130 | 136 | 140 | 144 | 147 | 149 |
| | 1% | 107 | 135 | 158 | 176 | 191 | 204 | 215 | 224 | 233 |
| Flat terrain | 0 | 124 | 166 | 202 | 236 | 266 | 295 | 322 | 348 | 373 |
| Downhill | -1% | 139 | 192 | 242 | 291 | 337 | 383 | 428 | 473 | 517 |
| | -2% | 154 | 221 | 286 | 352 | 416 | 482 | 548 | 613 | 678 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20012 • ID 17.5 mm • Kd 0.10 • Flow rate 1.60 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 75 | 92 | 105 | 115 | 122 | 127 | 133 | 136 | 139 |
| | 1% | 85 | 109 | 128 | 145 | 158 | 170 | 182 | 192 | 200 |
| Flat terrain | 0 | 95 | 127 | 154 | 180 | 203 | 225 | 246 | 266 | 286 |
| Downhill | -1% | 103 | 142 | 177 | 211 | 244 | 276 | 307 | 338 | 368 |
| | -2% | 112 | 158 | 202 | 246 | 289 | 331 | 374 | 418 | 461 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20012 • ID 17.5 mm • Kd 0.10 • Flow rate 2.10 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 66 | 82 | 94 | 104 | 112 | 118 | 123 | 128 | 131 |
| | 1% | 73 | 94 | 111 | 126 | 139 | 150 | 161 | 170 | 179 |
| Flat terrain | 0 | 79 | 107 | 130 | 152 | 171 | 190 | 207 | 224 | 241 |
| Downhill | -1% | 85 | 117 | 146 | 173 | 199 | 225 | 250 | 274 | 298 |
| | -2% | 91 | 128 | 163 | 197 | 230 | 263 | 296 | 329 | 361 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20012 • ID 17.5 mm • Kd 0.10 • Flow rate 4.20 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 45 | 58 | 68 | 77 | 84 | 91 | 96 | 101 | 105 |
| | 1% | 48 | 63 | 76 | 87 | 97 | 106 | 114 | 121 | 128 |
| Flat terrain | 0 | 51 | 68 | 83 | 98 | 110 | 123 | 133 | 144 | 155 |
| Downhill | -1% | 53 | 72 | 90 | 106 | 121 | 136 | 150 | 164 | 178 |
| | -2% | 56 | 77 | 97 | 116 | 134 | 151 | 169 | 185 | 203 |

Max. lateral length (meters) at different slopes - 10% flow variation

Leach Line™ X • 20012 • ID 17.5 mm • Kd 0.10 • Flow rate 8.40 l/h • Inlet pressure 1.5 Bar

| | Distance between drippers (meter) | | | | | | | | | |
|--------------|-----------------------------------|------|------|------|------|------|------|------|------|------|
| | Slope | 0.20 | 0.30 | 0.40 | 0.50 | 0.60 | 0.70 | 0.80 | 0.90 | 1.00 |
| Uphill | 2% | 30 | 40 | 47 | 54 | 60 | 65 | 70 | 74 | 78 |
| | 1% | 31 | 42 | 50 | 59 | 65 | 71 | 78 | 83 | 89 |
| Flat terrain | 0 | 33 | 44 | 54 | 63 | 71 | 78 | 86 | 93 | 100 |
| Downhill | -1% | 33 | 45 | 56 | 66 | 75 | 84 | 93 | 101 | 109 |
| | -2% | 34 | 47 | 59 | 70 | 80 | 90 | 100 | 110 | 119 |

06-0524DRP-PST-0052-EN